




TABLE-TOP PRINT & APPLY LABEL APPLICATOR SYSTEM

Heavy Duty Industrial Design
Print Speeds up to 16 Inches/Sec
System Widths of 4.5" & 6.5"
Thermal Transfer & Direct Thermal
203, 305 or 600dpi Print Resolution
12" Label Storage Spools
Label Dispenser
Tamp Applicator
Round Product Applicator
User-Friendly Operating Software
Hand Held Touch Screen Interface
Zebra or Sato Print Engines
Optional Smart Tamp
System & Batch Counters



sales@dartronics.com

LM4012TTPAS

TABLE-TOP PRINT & APPLY LABEL APPLICATOR SYSTEM

STANDARD APPLICATOR SPECIFICATIONS

LABELING SPEED / THROUGHPUT RATE
UP TO 45 PER MINUTE

INTERFACE SENSORS
PRODUCT SENSOR - PHOTOEYE / LIMIT SWITCH / PLC INPUT
AUXILIARY OUTPUT WITH CONNECTOR

LABEL PLACEMENT TOLERANCE
UP TO +/- 1/32" WHEN LABELS ARE PRODUCED TO SPECIFICATIONS & PRODUCT HANDLING IS CONTROLLED

ELECTRICAL INPUT
90-220VAC / 60HZ -- 5 AMPS

LABEL ROLL CAPACITY
12" MAX OUTSIDE DIAMETER, WOUND ON A 3" CORE. DIE-CUT WASTE REMOVED WITH A MINIMUM 1/8" SEPARATION BETWEEN LABELS

AIR REQUIREMENTS
80 PSI / 3 CFM REQUIRED

ACCEPTABLE LABEL SIZES
MINIMUM 1.0" WIDE x 1/2" LONG
MAXIMUM 6.5" WIDE x 14" LONG (OPTIONAL SIZES AVAILABLE)

APPLICATION METHODS
ROUND, TAMP, SMART TAMP, FLAG & DISPENSER

ENVIRONMENT
OPERATING 50-95 DEGREES F (10-35 DEGREES C)
15-85% RELATIVE HUMIDITY, NON-CONDENSING

FOOTPRINT
36" WIDE x 20" DEEP x 26" HIGH


WEIGHT
APPROXIMATELY 125LBS.

OPTIONAL FEATURES


- 6-1/2" WIDE LABEL MAXIMUM
- 203, 305, & 600 DPI PRINT QUALITY
- WIRELESS INTERFACE TO PRINT ENGINE
- SMART TAMP APPLICATOR MODULE
- CUSTOM PRODUCT FIXTURES
- TAPERED ROLLERS
- ALARM STACK/SYSTEM STATUS TOWER
- CUSTOM PROGRAMMING




-ROUND MODULE-



-TAMP MODULE-



-CUSTOM FIXTURES-



Dartronics, Inc.

150 William Street, Perth Amboy, NJ 08861

732-324-0800 | 1-800-298-8936

www.dartronics.com

sales@dartronics.com

This datasheet is for informational purposes only. MM2 makes no warranties, expressed or implied in this summary. Specifications are subject to change without notice. LabelMill is a registered trademark of Mills Machine II, Inc. © 2022 MM2. All rights reserved.