



Distributed by  
**DARTRONICS, INC.**  
PACKAGING AUTOMATION SPECIALISTS



# BEL 5252u


Semi-Automatic Form, Pack & Seal System  
Up to 15 cases per minute



**RSC Case**  
The BEL 5252u  
seals RSC cases.



## Semi-Automatic Form, Pack & Seal System



### Squareness Assured

BEL's innovative and powerful Uni-Drive system synchronizes conveyor belt speed, eliminating case skew, so that cases leave the machine squarely taped.



### Ultra Safe Flap Folder

Snap Folder flap-folding technology safeguards personnel by eliminating the traditional "flap kicker", which can cause serious injury and the need for expensive machine guarding.

patent #5,440,852



### Easy Set-up Guides

A color-coded pictorial guide means convenient setup and quick change-over in seconds, Spanish and French language instructions are available.



### Superior Tape Application

The BEL 5252u is equipped with state-of-the-art DEKKA High Performance tape heads that are easily loaded in or out of the machine in 30 seconds or less.

patent #5,735,101

Form Pack Seal

# BEL 5252u Semi-Automatic Form, Pack & Seal System

## BEL 5252u Features

- Energy smart features such as Power Save Mode reduce operating costs associated with unattended machinery running.
- Electro-pneumatic system provides greater control over the forming of corrugated with higher recycled content.
- Illustrated, color-coded adjustment guide assists operator with changeovers and minimizes changeover time.
- Built-in box stand keeps case blanks handy for the operator, providing increased through-put and enhanced ergonomics by minimizing the operator reaching and twisting during packing.
- Anodized aluminum frame construction eliminates unsightly machine wear and extends machine life.
- Unitized frame design provides ease of mobility and greater machine life.

## Complete Solution



**A32 Accumulation Table**  
Rotary turntable that presents product to the operator for packing. Features an adjustable speed motor.



**Nestaflex Conveyor**  
Nestaflex conveyors are flexible units that can be lengthened, shortened or curved to fit changing packaging situations.

## BEL 5252u Specifications

Case Size Range	Length	Width	Height
Minimum	8" 203 mm	5" 127 mm	5" 127 mm
Maximum	26" * 660 mm	18" 457 mm	16" 406 mm
<b>Infeed/Outfeed Height (with adjustable leg extensions)</b>			
Frame	22" (559 mm)		
Minimum	25" (635 mm)		
Maximum	32" (813 mm)		
Machine Speed: Up to 15 cases per minute. Oversize model available. Consult factory for case size ranges.			

\*Automatic top flap folding is limited to 22" maximum case length; longer cases are run with the folders in manual mode.

\*\* Standard automatic top flap folding is limited to 15.5" maximum case width; cases up to 18" wide are run with the folders in manual mode or in automatic mode with a modification option that reduces maximum case height capability to 15".

Specifications are subject to change without notice.

Backed by Wexar's warranty and experienced, nationwide service team.

## How the BEL 5252u Works



**RSC Case**  
The BEL 5252u seals RSC cases.



### 1 Form

The operator inserts a case blank. The BEL 5252u folds the bottom flaps. Cases are positioned for packing and easy transfer to case sealer.



### 2 Pack

The BEL 5252u holds the case in place for efficient "hands free" loading. When fully loaded, the operator easily pushes the case into the case sealer.



### 3 Seal

Case flaps are automatically folded with BEL's safe *Snap Folder* technology. The sealer then tapes the top and bottom flaps.



**DARTRONICS, INC.**

PACKAGING AUTOMATION SPECIALISTS



Dartronics, Inc.  
150 William Street  
Perth Amboy, NJ 08861

Phone: 732-324-0800  
sales@dartronics.com  
www.dartronics.com

a division of Pro Mach