

Semi-Automatic Stretch Wrapping Machine Survey

January, 2022

Customer Information
Date:
Company:
Address:
City: State: Zip:
Telephone: FAX:
Email Address:
Contact Name:
Company:
Address:
City: State: Zip:
Telephone: FAX:
Email Address:
Contact Name:
Model of stretch wrapper (if known):
If unknown please check model(s) of interest:
Entry level turntable model
Medium to high volume semi-automatic turntable
Medium to high volume platform (stand-alone) automatic turntable
Medium to high volume semi-automatic rotary tower model
Medium to high volume (stand-alone) automatic rotary tower

Pallet Load Information
Describe the product load:
How is the pallet loaded: Forklift Only Pallet Jack Only
Electric Walkie Extended Electric Walkie
Current process rate: Loads per Hour (Note: Min. 1 load/hr.)
Desired process rate: Loads per Hour (Note: Min. 1 load/hr.)
Indicate the stability of the pallet load:
Stable
Unstable
Unstable or fragile
The top layer of the load is: Full Partial Uneven
The stacking pattern is: Column Interlocked Other
Color of loads: Dark (Black) Shiny Light Clear Voids
Load Type:
Type A Type B Type C
Pallet Load Size Width Length Height Weight Production %
Maximum
Average
Minimum

Note: If no load information is provided quote will be BUDGETARY.

Wrapping Information
Desired number of bottom wraps: Desired number of top wraps:
Desired inches of overwrap at top of the load: Desired inches of film overlap:
Is the pallet to be wrapped with the load: Yes No (Note: Min. wrap height of LP models = 2.5")
Desired film prestretch level: (260% Standard on most models):
What brand/gauge stretch film will you be using:
What width of stretch film will you be using: 20" 30" Other:
Quote Insta-Cut Film Severance: Yes No (Note: Not available in Canada)
Environment Information
Location: Enclosed Building Open-sided Building Outdoors
Other environmental conditions:
Are there any special environmental considerations such as:
Moisture Dust Corrosive Wash-down
Cold room Freezer Other
Site temperature: °F max. °F min. °F typical
Utilities Information
Is dedicated 115V/60/20A electrical service available: Yes No
Other available voltage Phase Amp
80PSI @3CFM Compressed air available (A models only): Yes No
Customer Application Specification (Provide current application times for accurate throughput calculation)
Machine Loading: Seconds (Avg. 30 seconds)
Film Attachment: Seconds (Avg. 15 seconds)
Film Cut-Off: Seconds (Avg. 15 seconds)
Machine Un-Loading: Seconds (Avg. 30 seconds)
Comments

Dartronics, Inc. I 150 William Street Perth Amboy, NJ 08861 I (800) 298-8936 I Fax (732) 324-4488 E-mail: sales@dartronics.com I Web: www.dartronics.com