



CASE FORMING MADE EASY

The EX-CF Case Former from Eastey is designed for semi-automatic case forming and packing. The durable design has proven to keep production and maintenance efforts to a minimum to improve your case packing process. The EX-CF Case Former provides a fast and cost-efficient alternative to manual case forming.

EASY OPERATION

The EX-CF Case Former enables a single operator to form, pack, and seal corrugate cases. Operation is simple: open the case and place it in the top of the case former. Pneumatic switches activate the machine's flap folding mechanism to fold the bottom major and minor flaps. Once the flaps are folded, the case will stay in place while the case is filled by the operator. Filled cases can then be advanced into a taper for automated top and bottom casesealing.

INCREASED PRODUCTIVITY

EX-CF Case Former offers fast and easy case size changes with adjustable hand-crank side rails to accommodate boxes 8" to 25.5" in length, 6" to 19" wide, and 3.5" tall and greater.

COMPACT CASE FORMING AND PACKAGING

Designed for semi-automatic case forming and packing, the EX-CF will improve productivity and increase your ROI

INDUSTRIAL QUALITY

Each EX-CF machine is made from sturdy 12 gauge steel, high quality construction, and a powder coated exterior to protect the machine from abusive conditions for guaranteed years of use. The EX-CF will be a workhorse in your industrial case packing operation.

INCREASE YOUR ROI

The use of Eastey's EX-CF case forming machine can be learned in minutes, avoiding breaks in production and downtime. FOr increased efficiency, EX-CF Case Former can be combined with any Eastey Case Taper for automated case sealing.


THE RIGHT SOLUTION


Rugged design. Proven reliability. Simple operation. Your benefits go on and on. When it comes to industrial operation, rely on Eastey to provide the right solution for your case sealing needs.



EX-CF CASE FORMER













- 1. Stainless steel wear surfaces
- 2. Easy case size changes with adjustable folding/ revolving crank handle
- 3. Air only operation with emergency stop
- 4. Adjustable foot extensions for level setup, or optional caster for movement within your plant

EV_	CE.	FEA		D	e
			ΛU		

- Plug-in and go operation
- Adjustable side guides
- Adjustable foot extensions
- Fast and easy box size changes

ē

- Low maintenance
- Accommodates wide case range
 Roller extension included for wide boxes
- Small exit roller table included

EX-CF SPECIFICATIONS

Machinery Makeup	Industrial strength 12 gauge steel, powder coated for durability				
Conveyor Height Adj.	23.75" (603mm) to 29.75" (756mm) with leveling legs; 27.25" (692mm) to 33.25" (845mm) with optional casters				
BOX SPECIFICATIONS		Length	Width	Depth	
Minimum Box Size		8" (203.2mm)	6″ (152.4mm)	3.5″ (88.9mm)	
Maximum Box Size		25.5″ (647.7mm)	19" (482.6mm)	Unlimited	
Air Requirements 80 PSI					
Electrical Requirements	None				
Agency Approvals CE Certification					

27.6" - 32.3"





150 Williams Street, Perth Amboy, NJ 08861 Phone: (732) 324-0800 Fax: (732) 324-4488 Email: sales@dartronics.com